

- 3/2-way isolation valve
- Minimal dead volume
- With integrated power reduction
- Modular concept for various contacting options



TECHNICAL DATA


Function	3/2 Uni
Pneumatic connection	Flange
Orifice size	2 mm
Weight	40 g
Mounting position	any
IP protection class (scope of delivery)	IP40
Operating pressure	-0.8 – 3 bar(g)
Pressure resistance	> 4,5 bar(g)
Flow rate with air @ max. pressure	> 49 l/min
Flow coefficient kv	max. 0.09 l/min
Temperature range, environment	0 – 50 °C
Temperature range, medium	0 – 50 °C
Temperature range, storage	0 – 50 °C
Media quality	≤ 5 µm
Media	Air and liquids



ELECTRICAL DATA

Electrical connection	Connector housing
Length electrical connection	300 mm
Nominal voltage	12 V DC
Nominal power consumption	1 W

INTEGRATED CIRCUIT




Startup power consumption
 for approx. 80 ms: 5.2 W


WETTED MATERIALS

Housing	PEEK
Seal o-ring	EPDM
Seal anchor	EPDM


PNEUMATIC SYMBOL



VALVE DIMENSIONS



INTERFACE DIMENSIONS



ACCESSORIES

Base plate



M6-Thread: 809-000-005
 1/4-28 UNF: 809-000-006

The technical information given describes the usual properties of our products and does not constitute a warranty statement. All values were determined under laboratory conditions and must be verified by the customer for his specific purpose. Due to continuous technical progress, all rights to changes and additions are reserved.
 Status: 2026-04-02